1&I Inflow and Infiltration



PRIVATE PROPERTY SOURCES AND SOLUTIONS

PLANT DESIGN CRITERIA

Parameter	Design Criteria 2026
FLOW, mgd	
Average	0.75
Maximum Month (1.8:1)	1.21
Maximum Day (4:1)	2.68
Peak Hour (4.5:1)	3.00
BOD, Ibs/day	
Average	1458
Maximum Month (1.1:1)	1604
Maximum Day (2:1)	2916
TSS, lbs/day	
Average	1661
Maximum Month (1.1:1)	1827
Maximum Day (2:1)	3322
PHOSPHORUS, Ibs/day	
Average	47
Maximum Month (1.1:1)	52
Maximum Day (2:1)	94
TKN, lbs/day	
Average	182
Maximum Month (1.1:1)	200
Maximum Day (2:1)	364

Village of Kewaskum

Population Aprox. 4,000

Average Daily Flow .4 mgd

The Problem

- During significant rain events, storm and ground water can find its way into the sanitary sewer system through inflow and infiltration (I&I). When this excess water enters the sanitary sewer system, it can create the following problems:
- Overloading of collection system resulting in basement backups
- Additional cost to treat the higher volume of wastewater
- Reduced treatment efficiency due to exceedance of treatment process designs.
- Potentially exceeding permit compliance (TMDL)

Construction Age of Homes Impact on 1&1

Homes built prior to 1920 may not have foundation drains installed


Homes built after 1954 were not allowed to connect foundation drains to the sanitary sewer due to change in plumbing code.

1920 and 1954


1920

1954

Homes built between 1920 and 1954 may have foundation drains that discharge to the sanitary sewer lateral







Drain Tile Cross Connection

- Drain tile directly connected to sanitary sewer lateral was common between 1920 and 1954.
- Palmer Valves commonly used for this connection.
- Some directly tied into sanitary lateral at foundation wall
- World War II ended in 1945. Why is this important?

Floor drain with Palmer valve cross connection



The Kewaskum Approach

- New Sanitary Sewer
- New Water Main
- New Storm Sewer
- Storm Laterals Provided To Each Property. Connection REQUIRED
- Pipe Burst Sanitary Laterals
- Remove Clearwater Cross Connections and Install Sump Pumps as Needed.

Village Code

Sec. 14-331. Sump pump regulations.

- (b) Restrictions. Except as otherwise provided in this section, where existing sump and storm water drainage lines exist, all sump pump discharges shall be connected directly to a storm sewer by means of an underground closed pipe.
- (c) Prohibited sanitary sewer discharges. The connection of roof downspouts, sump pump discharges, exterior foundation drains, area drains, or other sources of surface run off or ground water to a building sewer or drain which discharges directly to a public sanitary sewer is prohibited. The connection of roof down spouts, or other sources of direct surface run off discharge is prohibited to the sump pump discharge piping system.
- (d) Time for connection.
 - (1) New construction connections.
 - (2) Existing building connections.
 - a. In the event of a new installation, or underground piping becoming available, existing sump pump discharge lines shall be connected within 45 days of the lateral being available.

Sec. 94-251. Unpolluted waters and stormwater.

(a) No person shall discharge or cause to be discharged any unpolluted waters such as stormwater, groundwater, roof runoff, subsurface drainage or cooling water to any sanitary sewer

Private Property Involvement

Identify problem areas through age of home, CCTV inspections, other infrastructure deficiencies, and areas where homeowners have already needed to fix collapsed laterals.



Public meeting to explain project, set up appointments for inspections, and discuss financing options.



Inspect homes for existing condition



Assist contractors during construction



Consent and waivers for work to be completed. 100%

Participation

Home Inspections

- Sump pump and discharge location
- Number of floor drains and do they have cross connections
- Location of sanitary lateral cleanout
- Any special features to the property

Conclusion

I/I is the single largest contributing component to impending TMDL discharge limits.

Major source of I/I comes from private properties and in particular foundation drains and sump pumps.

Foundation drain cross connection elimination requires a lot of effort but has the greatest return on investment.


Communities are starting to see significant reductions in I/I through partnering with private property owners.



Funding for high flow optimization

FOCUS ON ENERGY ASSISTANCE

Goal



Flow Equalization Through Lift Station VFD Addition

Average plant flow rate 250 GPM

Hwy 45 Lift Station flow rate

Prior to VFD

650GPM

After VFD

Variable not to exceed 300GPM

Focus on Energy Incentive



VFD Implementation for Lift Station Pumps



 Recently installed variable frequency drives (VFDs) on two 75HP lift station pumps to improve motor efficiency.




• Results: Annual energy savings of 221,911 kWh, reducing energy costs by more than \$24,400.



• Financial Incentives: Received \$6,600 to support the project

Aeration Basin Diffuser Replacement Focus on Energy Incentive

- ▶ Replacing outdated ceramic disk finebubble diffusers with new flexible membrane fine-bubble diffusers.
- ▶ Results: Improved oxygen transfer efficiency, reduced blower pressure, and lower airflow requirements.
- ▶ Estimated Savings: 64,191 kWh and 8.43 kW annually.
- Estimated Incentive: \$4,457.81




Aeration Basin Automated control valves



• Installing automated control valves to optimize air pressure and distribution across the system.



Anticipated incentive \$7,037.43



Project	Cost	Focus Incentive
VFD install at Lift station	\$21,935	\$6,600
Aeration Diffuser replacement	\$19,940	\$4,457
Automated Aeration control Valves	\$22,860	\$7,037
Totals	\$64,735	\$18,094

Project Cost and Incentive Totals

Thank You!

- Ben Propson
- Village of Kewaskum WWTF Supervisor
- bpropson@kewaskumwi.gov





Wisconsin Wast Operators Asso

City of Sun Prairie

Jeremy Cramer Wastewater Conveyance and Treatment Director





Wastewater Treatment Plant


1982 Original Facility Built
 Population 13,417

2005 Liquids and Solids Upgrade
 Population 25,173

Phosphorus Upgrade


Population 35,967

2025 Solids UpgradePopulation 39,419





Collection System






Walker/Castle Inflow Event Plan


















































- Grouting manholes
- Bench repairs
- Road and ring repairs










GIS



Treatment Plant




			2016	2017	2018	2019	2020	2021	2022	2023	2024						$\overline{}$				
	Population	n	2010	2011	2010	34926				38387	39149										
Cost per lb BOD removed			\$0.091	\$0.088	\$0.084	\$0.074	\$0.073	\$0.067	\$0.072	\$0.064	\$ 0.054	1800									
Average kWh per day			6780	6799	7096	7387	7754	7277	7298	7307	6559										
Total charges per kWh			\$0.070	\$0.074	\$0.066	\$0.066	\$0.068	\$0.073	\$0.079	\$0.073	0.072	1600									
kWh per 1000 PE			80045	77339	78488	77672	80225	73198	71406	69490	60736	1400									
MWh/MG			1.69	1.64	1.77	1.76	1.96	2.31	2.29	2.15	1.66										
kWH/1000lb of BOD/yr			1279	1640	1229	1110	1065	929	909	873	742	<u></u>									
MG/Year			1,466	1,509	1,461	1,545	1,450	1,144	1,163	1,241	1445	98									
kWh/MG/Year			1693	1640	1773	1759	1957	2309	2290	2148	1657	= 1000 0									
\$/MG/Year			\$118.89	\$120.98	\$117.84	\$116.11	\$133.41	\$167.69	\$181.17	\$157.31	\$ 119.01	10 800									
kWh/person/year			80.04	77.34	78.49	77.67	80.22	73.20	71.41	69.49	60.74	1200 900 1000 1000 800									
Focus	on Energy	Benchmark	1650	1650	1650	1650	1650	1650	1650	1650	1650	≤ 600									
												400									
WI Avg WWTP Energy Use											400										
Activated S	1-5 mgd		kW/1000 II	b BOD								200									
			kw/MGD	DE																	
Best Practi	cos Bonck		kWh/1000	PE								0	2016	2017	2018	2019	2020	2021	2022	2023	2024
Activated S			kw/MGD	Avg									2010	2017	2010	2013	2020	2021	2022		2024
Activated C	1-5 mga	1510		Top 25%																	
		1650			ices Bench	mark															
250	0											90000									
												80000									
200	0											80000									
												70000								_	
	-											60000									
<u></u> 유 150	0											PE									
$ \check{\succeq}$												<u> </u>									
— Q 1500 — W/4 — 1000												0000 50000 40000 WW									
_ ≤ 100	0											- ₹									
												30000									
50	0											20000									
												10000									
	0											0									
	2016	2017	2018	2019 202	20 2021	2022	2023	2024					2016	2017	2018	2019	2020	2021	2022	2023	2024
																					40

Monitor Influent Flow vs Drinking Water pumped

Drinking Waterflow

Water and Wastewater Flows















SUNSTAINABLE BIOSOLIDS

Addresses Single Points of Failure





Provides

- Redundancy
- Efficiency
- Many Class A options to off ramp at

No extra staff needed



Farming Practices Have Changed – (Soil loss, compaction and lack of organic matter a major issue)

Not conducive to Class B biosolids application

No till

Minimum till

Strip till

















Make Hot Water to dry Biosolids

Use the sun





Class A Biosolids Uniform size and density



In the field

Work out in the field - Source and Blueprint









